



TorchLED torch light „SBB“ – Safety guard
battery or accu operated



Technical data lamp

Power supply: 4 pcs AA 1.5 V batteries (3'000 mA) or
4 pcs AA 1.5 V accu cells (1'900 mA)

Luminous flux: 90 lm (1 LED white full light)

Protection category: IP54

Light source: LED

Equipment: 1 x white / 7 x red

Housing: – PA6-housing, with rubber overmolded
handle lots (non-slip)
– freestanding
– belt clip (chrome steel)
– mechanical resistant
– signal colour yellow
– integrated attachment points for hand
strap and belt

Temperature range: –20° C to +45° C

Dimension (L x W x H): 68 x 115.5 x 35 mm

Weight: approx. 115 g without cells

Technical data charging station

Operating voltage: 100-240 VAC / 12-48 VDC

Power supply: 700 mA charging current

Protection class: IP44

Housing: – ABS
– wall or table mounting possible
– lamp retaining clip
– cut-outs on the underside of the
housing prevent cable kinking
and breakage

Contacts: spring steel, gold plated

Charging time: at 1'900 mAh cells max. 5 h



Temperature range: 0° C to +40° C

Dimension (L x W x H):
– Charging station: 86.6 x 79.6 x 44 mm
– 5-fold charging station: 500 x 220 x 125 mm

Features

Red light appears each time a button is pressed. This enables trains to be stopped quickly in an emergency in accordance with the SBB manual. The luminaire also includes integrated white light. It can also be used as a torch. The unmistakable operation of the switching element through colour coding enables work to be carried out safely in marshalling yards. It is easy to handle even when wearing winter gloves.

Function

- 
On/Off
 - tap: Switching the light on and off
 - when switched on, all red LEDs light up
 - operation with white light, Switch to red light
 - further operation switches light off
- 
On/Function selection
 - tap: Switching red light on
 - further operation switches to white light
 - each further operation switches between white and red light

Item no.	Designation
✓ 125385	TorchLED torch light, work and inspection light, 1 x LED white / 7 x LED red

Accessories / spare parts	
✓ 860276	TorchLED charging station, 100-240 VAC, incl. 1.5 m cable with plug-in transformer
✓ 861085	TorchLED charging station, 12-48 VDC, incl. 1.5 m cable with cigarette plug
✓ 860440	TorchLED charging station, 12-48 VDC, incl. 1.5 m cable without plugs and sockets
✓ 130407	TorchLED wall charging station 5-fold, 100-240 VAC / 700 mA, max. 15 VDC, incl. 3 m main supply 3 x 1.0 mm² black T12
✓ 860274	Accu-NiMH 1.2V / 1900 mAh HR6-AA
✓ 860275	Alkaline battery 1.5V / LR6-AA
✓ 168655	Magnetic foil 60 x 20 x 2 mm
✓ 128785	Wall bracket – empty
✓ 860335	TorchLED belt pouch 72 x 127 x 35 mm

For a TorchLED Railway, art. 860274 or 860275 is 4 x needed.

✓ from stock, offer subject to prior sale